

TESSERA

PROPERTIES

DESCRIPTION

European, embossed, semi aniline leather.

AVERAGE HIDE SIZE

55 sq ft

THICKNESS

1.2 mm +/-0.1 mm

WEIGHT

2.75 oz +/-0.25 oz per sq ft

ATTRIBUTES

Combination tanned for optimal pattern integrity and antiques for depth of color. Flame resistant and UV protected. Water and stain repellent finish.

HORIZONTAL REPEAT

1/8 inch

VERTICAL REPEAT

1/8 inch

GRAIN CHARACTERISTICS

Embossed

FINISH CHARACTERISTICS

Durable, antique finish

Declare.



TEST PERFORMANCE

ABRASION

CS-10 Taber Abrasion Resistance:
1600 cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes
on Textile Materials (Quantitative):
Meets Requirements

AATCC 147

Assessment of Antibacterial Activity
of Textile Materials (Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

California AB 1817

Product Safety: Textile
Articles: Perfluoroalkyl and
Perfluoroalkyl Substances
Complies

FLAMMABILITY

California AB 2998
Consumer Products:
Flame Retardant Materials:
Not Applicable

California Technical Bulletin
117 2013 Section Flammability Test:
Certified

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(ii) Federal Aviation Regula-
tion for Flammability Resistance:
Passes with flame treatment

MVSS 302
Federal Motor Vehicle Safety Standards
Flammability of Interior Materials:
Certified

IMO Part 8: Upholstered Furniture
International Marine Organization
3.1 Cigarette Ignition:
Passes

IMO Part 8: Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passes

NFPA 260
National Fire Protection Association
Cigarette Ignition Resistance:
Certified

BS 5852:2006:Source 5
British Standard Flammability Test:
Certified

ASTM E84
Surface Burning Characteristics of Building
Materials:
Class A

DURABILITY Excellent. Recommended for all upholstery applications.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/MGG
UL 2818



LeatherShield™



Antibacterial



FiberDye®

GARRETT

LEATHER

800.342.7738
garrettleather.com