

PROPERTIES

DESCRIPTION

European natural grain, semi-aniline leather.

AVERAGE HIDE SIZE

50 sq ft

THICKNESS

1.1 mm +/- 0.1 mm

ATTRIBUTES

Durable, waterproof finish with hand-mottled distressed appearance. Unique variations and natural markings appear throughout each hide. Antibacterial and UV protected. Stain and scratch resistant.

WEIGHT

2.75 oz. +/- .25 oz per sq ft

GRAIN CHARACTERISTICS

Natural variations

FINISH CHARACTERISTICS

Durable, hand mottled.

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.

Cherish is LBC Red List Approved.

TEST PERFORMANCE

ABRASION

ASTM D-4157

Wyzenbeek Abrasion Resistance:

Class 4.5 at 100,000 cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes on Textile Materials (Quantitative):

Meets Requirements

AATCC 147

Assessment of Antibacterial Activity of Textile Materials (Qualitative):

Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold

Indoor Air Quality:

Certified

LIGHTFASTNESS

AATCC 16.3 Opt 3

Colorfastness to Light:

Class 5 at 72 hours

WATER RESISTANCE

Hydrostatic Pressure Test, AATCC 127

270+ cm

FLAMMABILITY

California AB-2998;

Consumer products -

Flame Retardant Materials:

Not Applicable

California Technical Bulletin

117 2013 Section 1 Flammability Test:

Certified

FAR 25.853 (a) Am. 25-116, App. F,

Part I (a)(1)(ii) Federal Aviation

Regulation for Flammability Resistance:

Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety Standards

Flammability of Interior Materials:

Certified

IMO Part 8: Upholstered Furniture

International Marine Organization

3.1 Cigarette Ignition:

Passed

IMO Part 8: Upholstered Furniture

International Marine Organization

3.2 Propane Flame:

Passed

NFPA 260

National Fire Protection Association

Cigarette Ignition Resistance:

Certified

BS 5852:2006:Source 5

British Standard Flammability Test:

Certified

ASTM E84

Surface Burning Characteristics

of Building Materials:

Class A

Cherish may be used in California TB

133 applications with suitable fire backers.

DURABILITY

 Excellent. Recommended for all upholstery applications.

PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye®

GARRETT.

LEATHER

800.342.7738

garrettleather.com