

BELLISSIMO

PROPERTIES

DESCRIPTION

Italian full grain, semi-aniline leather.

AVERAGE HIDE SIZE

50.00 sq ft

THICKNESS

1.2 mm +/-0.1 mm

ATTRIBUTES

Natural grain with distressed appearance and scratch resistant finish. Antibacterial and UV protected. Water and stain repellent dyed into the leather.

WEIGHT

3.0 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Natural variations

FINISH CHARACTERISTICS

Scratch resistant finish

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.



TEST PERFORMANCE

ABRASION

ASTM D-4157
Wyzenbeek Abrasion
Resistance:
Class 5 at 100,000 cycles

ANTIBACTERIAL

AATCC 100
Assessment of Antibacterial
Finishes on Textile
Materials (Quantitative):
Meets Requirements

AATCC 147
Assessment of Antibacterial
Activity of Textile Materials
(Qualitative):
Meets Requirements

ABSORPTION

ASTM D751
Water Resistance
Hydrostatic Pressure Test:
Exceeds Requirements
270+ cm

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

California AB 1817
Product Safety: Textile
Articles: Perfluoroalkyl and
Polyfluoroalkyl Substances
Complies

LIGHTFASTNESS

AATCC 16.3 Opt 3
Colorfastness to Light:
Class 4 at 72 hours

FLAMMABILITY

California Technical
Bulletin 117 2013
Section E Flammability Test:
Certified

California AB 2998
Consumer Products:
Flame Retardant Materials:
Not Applicable

FAR 25.853 (a) Am. 25-116, App.
F, Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability
Resistance:
Passes with flame treatment

MVSS 302
Federal Motor Vehicle Safety
Standards Flammability of
Interior Materials:
Certified

IMO Part 8:
Upholstered Furniture
International Marine
Organization
3.1 Cigarette Ignition:
Passed

IMO Part 8:
Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

NFPA 260
National Fire Protection
Association Cigarette Ignition
Resistance:
Certified

BS 5852:2006: Source 5
British Standard
Flammability Test:
Certified

*Bellissimo may be used in
California TB 133 applications with
suitable fire backers.*

DURABILITY Excellent. Recommended for all upholstery applications.

GARRETT.
LEATHER

800.342.7738

garrettleather.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye™