

BERKSHIRE

PROPERTIES

DESCRIPTION

Italian enhanced grain, semi-aniline leather.

AVERAGE HIDE SIZE

50.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Durable finish. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Uniform

FINISH CHARACTERISTICS

Durable

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.



TEST PERFORMANCE

ABRASION

CS-10

Taber Abrasion Resistance:
1,200+ cycles

ASTM D-4157

Wyzenbeek Abrasion
Resistance:

Class 4.5 at 100,000 cycles

ABSORPTION

ASTM D751

Water Resistance

Hydrostatic Pressure Test:
Exceeds Requirements
270+ cm

ASTM D-1913

Resistance to Wetting of
Garment-Type Leather:
Class 95

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial
Finishes on Textile
Materials (Quantitative):
Meets Requirements

AATCC 147

Assessment of Antibacterial
Activity of Textile Materials
(Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

California AB 1817

Product Safety: Textile
Articles: Perfluoroalkyl and
Polyfluoroalkyl Substances
Complies

LIGHTFASTNESS

AATCC 16.3 Opt 3

Colorfastness to Light:
Class 5 at 72 hours

FLAMMABILITY

California Technical

Bulletin 117 2013

Section E Flammability Test:
Certified

California AB 2998

Consumer Products:

Flame Retardant Materials:
Passes

FAR 25.853 (a) Am. 25-116, App.
F, Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability
Resistance:

Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety
Standards Flammability of
Interior Materials:
Certified

IMO Part 8:

Upholstered Furniture
International Marine
Organization

3.1 Cigarette Ignition:
Passed

IMO Part 8:

Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

NFPA 260

National Fire Protection
Association Cigarette Ignition
Resistance:
Certified

BS 5852:2006: Source 5
British Standard
Flammability Test:
Certified

ASTM E84

Surface Burning Characteristics
of Building Materials:
Class B

*Berkshire may be used in
California TB 133 applications with
suitable fire backers.*

DURABILITY Excellent. Recommended for all upholstery applications.

GARRETT

LEATHER



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye™



Guaranteed
In Stock

800.342.7738
garrettleather.com