

# CADENCE

## PROPERTIES

### DESCRIPTION

Italian enhanced grain, semi-aniline leather.

### AVERAGE HIDE SIZE

50.00 sq ft

### THICKNESS

1.1 mm +/-0.1 mm

### ATTRIBUTES

Durable, antibacterial finish. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

### WEIGHT

2.75 oz +/-0.25 oz per sq ft

### GRAIN CHARACTERISTICS

Uniform

### FINISH CHARACTERISTICS

Durable

### NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.



## TEST PERFORMANCE

### ABRASION

CS-10  
Taber Abrasion Resistance:  
1,000+ cycles

### ABSORPTION

ASTM D751  
Water Resistance  
Hydrostatic Pressure Test:  
Exceeds Requirements  
150+ cm

### ANTIBACTERIAL

AATCC 100  
Assessment of Antibacterial  
Finishes on Textile  
Materials (Quantitative):  
Meets Requirements

AATCC 147  
Assessment of Antibacterial  
Activity of Textile Materials  
(Qualitative):  
Meets Requirements

### ENVIRONMENTAL

GREENGUARD Gold  
Indoor Air Quality:  
Certified

### LIGHTFASTNESS

AATCC 16.3 Opt 3  
Colorfastness to Light:  
Class 5 at 72 hours

### FLAMMABILITY

California Technical  
Bulletin 117 2013  
Section E Flammability Test:  
Certified

California AB 2998  
Consumer Products:  
Flame Retardant Materials:  
Not Applicable

FAR 25.853 (a) Am. 25-116, App.  
F, Part I (a)(1)(ii) Federal Aviation  
Regulation for Flammability  
Resistance:  
Passes with flame treatment

MVSS 302  
Federal Motor Vehicle Safety  
Standards Flammability of  
Interior Materials:  
Certified

IMO Part 8:  
Upholstered Furniture  
International Marine  
Organization  
3.1 Cigarette Ignition:  
Passed

IMO Part 8:  
Upholstered Furniture  
International Marine Organization  
3.2 Propane Flame:  
Passed

NFPA 260  
National Fire Protection  
Association Cigarette Ignition  
Resistance:  
Certified

BS 5852:2006: Source 5  
British Standard  
Flammability Test:  
Certified

ASTM E84  
Surface Burning Characteristics  
of Building Materials:  
Class A

*Cadence may be used in  
California TB 133 applications with  
suitable fire backers.*

**DURABILITY** Excellent. Recommended for all upholstery applications.



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
UL.COM/GG  
UL 2818



LeatherShield™



Antibacterial



FiberDye®

GARRETT

LEATHER

800.342.7738  
garrettleather.com