CARESSA

PROPERTIES

DESCRIPTION

Italian natural grain, semi-aniline leather.

AVERAGE HIDE SIZE

55.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Light finish. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Natural variations

FINISH CHARACTERISTICS

Light

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.





TEST PERFORMANCE

ABRASION

CS-10

Taber Abrasion Resistance: 800+ cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes on Textile Materials (Quantitative): Meets Requirements

AATCC 147

Assessment of Antibacterial Activity of Textile Materials (Qualitative):

Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold Indoor Air Quality: Certified

California AB 1817 Product Safety: Textile Articles: Perfluoroalkyl and Polyfluoroalkyl Substances

LIGHTFASTNESS

Complies

AATCC 16.3 Opt 3 Colorfastness to Light: Class 5 at 72 hours

FLAMMABILITY

California Technical Bulletin 117 2013

Section E Flammability Test:

Certified

California AB 2998 Consumer Products:

Flame Retardant Materials:

Passes

FAR 25.853 (a) Am. 25-116, App. F, Part I (a) (1) (ii) Federal Aviation Regulation for Flammability

Resistance:

Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety Standards Flammability of

Interior Materials:

Certified

IMO Part 8:

Upholstered Furniture International Marine

Organization
3.1 Cigarette Ignition:

Passed

IMO Part 8:

Upholstered Furniture International Marine Organization

3.2 Propane Flame:

Passed

NFPA 260

National Fire Protection
Association Cigarette Ignition

Resistance:

Certified

BS 5852:2006: Source 5

British Standard Flammability Test:

Certified

ASTM E84

Surface Burning Characteristics of Building Materials:

Class A

Caressa may be used in California TB 133 applications with suitable

fire backers.

DURABILITY

Excellent. Recommended for all upholstery applications.











