

GLAZED

PROPERTIES

DESCRIPTION

Italian semi-aniline, natural grain leather.

AVERAGE HIDE SIZE

55.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Hand-antiqued with high gloss finish.
Flame resistant. UV protected. Water and stain repellent dyed into the leather.

WEIGHT

2.75 oz +/- 0.25 oz per sq ft

GRAIN CHARACTERISTICS

Smooth

FINISH CHARACTERISTICS

High gloss

TEST PERFORMANCE

ABRASION

CS-10

Taber Abrasion Resistance:
5,600 cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial
Finishes on Textile
Materials (Quantitative):
Meets Requirements

AATCC 147

Assessment of Antibacterial
Activity of Textile Materials
(Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold

Indoor Air Quality:
Certified

California AB 1817

Product Safety: Textile
Articles: Perfluoroalkyl and
Polyfluoroalkyl Substances
Complies

LIGHTFASTNESS

AATCC 16.3 Opt 3

Colorfastness to Light:
Class 5 at 72 hours

FLAMMABILITY

California Technical

Bulletin 117 2013
Section E Flammability Test:
Certified

California AB 2998

Consumer Products:
Flame Retardant Materials:
Not Applicable

FAR 25.853 (a) Am. 25-116, App.
F, Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability
Resistance:
Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety
Standards Flammability of
Interior Materials:
Certified

IMO Part 8:

Upholstered Furniture
International Marine
Organization
3.1 Cigarette Ignition:
Passed

IMO Part 8:

Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

BS 5852:2006: Source 5

British Standard
Flammability Test:
Certified

ASTM E84

Surface Burning Characteristics
of Building Materials:
Class B on MDF Backer

*Glazed may be used in California
TB 133 applications with suitable
fire backers.*

DURABILITY Excellent. Recommended for all upholstery applications.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye™

GARRETT

LEATHER

800.342.7738

garrettleather.com