

# KENYA

## PROPERTIES

### DESCRIPTION

Embossed nubuck, pure aniline leather.

### AVERAGE HIDE SIZE

60.00 sq ft

### THICKNESS

1.4 mm +/-0.1 mm

### ATTRIBUTES

Flame resistant. Water and stain repellent dyed into the leather.

### WEIGHT

3.50 oz +/-0.25 oz per sq ft

### GRAIN CHARACTERISTICS

Embossed

### FINISH CHARACTERISTICS

Naked

### NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

## TEST PERFORMANCE

### ABRASION

CS-10

Taber Abrasion Resistance:  
3,000 cycles

### ENVIRONMENTAL

GREENGUARD Gold  
Indoor Air Quality:  
Certified

California AB 1817  
Product Safety: Textile  
Articles: Perfluoroalkyl and  
Polyfluoroalkyl Substances  
Complies

### FLAMMABILITY

California Technical  
Bulletin 117 2013  
Section E Flammability Test:  
Certified

California AB 2998  
Consumer Products:  
Flame Retardant Materials:  
Not Applicable

FAR 25.853 (a) Am. 25-  
116, App. F, Part I (a)(1)(ii)  
Federal Aviation Regulation for  
Flammability Resistance:  
Passes with flame treatment

MVSS 302  
Federal Motor Vehicle Safety  
Standards Flammability of  
Interior Materials:  
Certified

IMO Part 8:  
Upholstered Furniture  
International Marine  
Organization  
3.1 Cigarette Ignition:  
Passed

IMO Part 8:  
Upholstered Furniture  
International Marine  
Organization  
3.2 Propane Flame:  
Passed

NFPA 260  
National Fire Protection  
Association Cigarette Ignition  
Resistance:  
Certified

BS 5852:2006: Source 5  
British Standard  
Flammability Test:  
Certified

ASTM E84  
Surface Burning  
Characteristics of Building  
Materials  
Class B

*Kenya may be used in California  
TB 133 applications with  
suitable fire backers.*

## DURABILITY

Recommended for moderate to low traffic areas.  
Crocking, or color transfer, may occur with excessive rubbing or exposure to moisture.



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
UL.COM/IGG  
UL 2818



LEATHER

800.342.7738  
garrettleather.com