

KEYHAVEN

PROPERTIES

DESCRIPTION

Embossed semi-aniline leather.

AVERAGE HIDE SIZE

54.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Durable. Flame resistant. UV protected. Water and stain repellent finish.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Embossed

FINISH CHARACTERISTICS

Hand finished

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

TEST PERFORMANCE

ABRASION

CS-10
Taber Abrasion Resistance:
1,000+ cycles

ANTIBACTERIAL

AATCC 100
Assessment of Antibacterial Finishes on Textile Materials (Quantitative):
Meets Requirements

AATCC 147
Assessment of Antibacterial Activity of Textile Materials (Qualitative):
Meets Requirements

ABSORPTION

AATCC 79
Absorbency of Textiles
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

California AB 1817
Product Safety: Textile Articles: Perfluoroalkyl and Polyfluoroalkyl Substances
Complies

LIGHTFASTNESS

AATCC 16.3 Opt 3
Colorfastness to Light:
Class 5 at 72 hours

FLAMMABILITY

California Technical Bulletin 117 2013
Section E Flammability Test:
Certified

California AB 2998
Consumer Products:
Flame Retardant Materials:
Not Applicable

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii) Federal Aviation Regulation for Flammability Resistance:
Passes with flame treatment

MVSS 302
Federal Motor Vehicle Safety Standards Flammability of Interior Materials:
Certified

IMO Part 8:
Upholstered Furniture
International Marine Organization
3.1 Cigarette Ignition:
Passed

IMO Part 8:
Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

NFPA 260
National Fire Protection Association Cigarette Ignition Resistance:
Certified

BS 5852:2006: Source 5
British Standard
Flammability Test:
Certified

Keyhaven may be used in California TB 133 applications with suitable fire backers.

DURABILITY

Excellent. Recommended for all upholstery applications.

GARRETT
LEATHER



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/GG
UL 2818



LeatherShield™



Antibacterial



FiberDye®

800.342.7738

garrettleather.com