

MYSTIQUE CROCO

PROPERTIES

DESCRIPTION

Italian natural grain, semi-aniline leather.

AVERAGE HIDE SIZE

60.00 sq ft

THICKNESS

1.3 mm +/-0.1 mm

ATTRIBUTES

Crocodile embossed, hand-tipped with durable finish. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

WEIGHT

3.25 oz +/- 0.25 oz per sq ft

GRAIN CHARACTERISTICS

Embossed crocodile

FINISH CHARACTERISTICS

Hand-tipped

APPROXIMATE PATTERN REPEAT

Vertical: 8.5"

Horizontal: 7"

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

TEST PERFORMANCE

ABRASION

CS-10

Taber Abrasion Resistance:

1,000 cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes on Textile Materials (Quantitative):

Meets Requirements

AATCC 147

Assessment of Antibacterial Activity of Textile Materials (Qualitative):

Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold

Indoor Air Quality:

Certified

California AB 1817

Product Safety: Textile

Articles: Perfluoroalkyl and

Polyfluoroalkyl Substances

Complies

LIGHTFASTNESS

AATCC 16.3 Opt 3

Colorfastness to Light:

Class 5 at 72 hours

FLAMMABILITY

California Technical

Bulletin 117 2013

Section E Flammability Test:

Certified

California AB 2998

Consumer Products:

Flame Retardant Materials:

Not Applicable

FAR 25.853 (a) Am. 25-116, App. F,

Part I (a)(1)(ii) Federal Aviation

Regulation for Flammability Resistance:

Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety Standards

Flammability of Interior Materials:

Certified

IMO Part 8:

Upholstered Furniture

International Marine

Organization

3.1 Cigarette Ignition:

Passed

NFPA 260

National Fire Protection Association

Cigarette Ignition Resistance:

Certified

BS 5852:2006: Source 5

British Standard

Flammability Test:

Certified

ASTM E84

Surface Burning Characteristics

of Building Materials:

Class B

Mystique Croco may be used in California

TB 133 applications with suitable fire

backers

DURABILITY

Excellent. Recommended for all upholstery applications, especially high traffic areas.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye®



LEATHER

800.342.7738

garrettleather.com