

PROPERTIES

DESCRIPTION

Embossed Italian semi-aniline leather.

AVERAGE HIDE SIZE

52.00 sq ft

THICKNESS

1.2 mm +/-0.1 mm

ATTRIBUTES

Embossed leather with hand antique finish for beautiful depth of color. Flame resistant. Water and stain repellent and antibacterial protection.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Embossed

FINISH CHARACTERISTICS

Hand antiqued finish

APPROXIMATE PATTERN REPEAT

Vertical: 59"
Horizontal: 59"

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare. 

TEST PERFORMANCE

ABRASION

CS-10
Taber Abrasion Resistance:
1,000+ cycles

ABSORPTION

ASTM D751
Water Resistance
Hydrostatic Pressure Test:
Exceeds Requirements
150+ cm

AATC 79-2010

Absorbency of Textiles
Meets Requirements

ANTIBACTERIAL

AATCC 100
Assessment of Antibacterial
Finishes on Textile
Materials (Quantitative):
Meets Requirements

AATCC 147

Assessment of Antibacterial
Activity of Textile Materials
(Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

California AB 1817
Product Safety: Textile
Articles: Perfluoroalkyl and
Polyfluoroalkyl Substances
Complies

FLAMMABILITY

California Technical
Bulletin 117 2013
Section E Flammability Test:
Certified

California AB 2998
Consumer Products:
Flame Retardant Materials:
Passes

FAR 25.853 (a) Am. 25-116, App.
F, Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability
Resistance:

Passes with flame treatment

MVSS 302
Federal Motor Vehicle Safety
Standards Flammability of
Interior Materials:
Certified

BS 5852:2006: Source 5
British Standard
Flammability Test:
Certified

IMO Part 8:
Upholstered Furniture
International Marine
Organization
3.1 Cigarette Ignition:
Passed

IMO Part 8:
Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

NFPA 260
National Fire Protection
Association Cigarette Ignition
Resistance:
Certified

Rill may be used in California TB
133 applications with suitable fire
backers.

DURABILITY Excellent. Recommended for all upholstery applications, especially high traffic areas.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/GG
UL 2818



LeatherShield™



Antibacterial



FiberDye®

GARRETT

LEATHER

800.342.7738
garrettleather.com