

BOLDERWOOD

PROPERTIES

DESCRIPTION

Embossed semi-aniline leather.

AVERAGE HIDE SIZE

54.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Durable. Flame resistant. UV protected.
Water and stain repellent finish.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Embossed

FINISH CHARACTERISTICS

Hand finished

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

TEST PERFORMANCE

ABRASION

CS-10 Taber Abrasion Resistance:
1000+ cycles

ABSORPTION

AATCC 79
Absorbency of Textiles:
Meets Requirements

ANTIBACTERIAL

AATCC 100
Assessment of Antibacterial Finishes
on Textile Materials (Quantitative):
Meets Requirements

AATCC 147
Assessment of Antibacterial Activity
of Textile Materials (Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

FLAMMABILITY

California Technical Bulletin 117 2013
Section E Flammability Test:
Certified

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability Resistance:
Passes with flame treatment

MVSS 302
Federal Motor Vehicle Safety Standards
Flammability of Interior Materials:
Certified

IMO Part 8: Upholstered Furniture
International Marine Organization
3.1 Cigarette Ignition:
Passed

IMO Part 8: Upholstered Furniture
International Marine Organization
3.2 Propane Flame:
Passed

NFPA 260

National Fire Protection Association
Cigarette Ignition Resistance:
Certified

BS 5852:2006: Source 5
British Standard Flammability Test:
Certified

*Bolderwood may be used in California
TB 133 applications with suitable fire
backers.*

DURABILITY Excellent. Recommended for all upholstery applications.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye®

GARRETT

LEATHER

800.342.7738
garrettleather.com