

PROPERTIES

DESCRIPTION

European natural grain, semi-aniline leather.

AVERAGE HIDE SIZE

50 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Durable, waterproof finish with hand-mottled distressed appearance. Unique variations and natural markings appear throughout each hide. Antibacterial and UV protected. Stain and scratch resistant.

WEIGHT

2.75 oz. +/-.25 oz per sq ft

GRAIN CHARACTERISTICS

Natural variations

FINISH CHARACTERISTICS

Durable, hand mottled.

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.

Cherish is LBC Red List Approved.

TEST PERFORMANCE

ABRASION

ASTM D-4157 Wyzenbeek Abrasion Resistance: Class 4.5 at 100,000 cycles

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes on Textile Materials (Quantitative): Meets Requirements

AATCC 147

Assessment of Antibacterial Activity of Textile Materials (Qualitative): Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold Indoor Air Quality: Certified

LIGHTFASTNESS

AATCC 16.3 Opt 3 Colorfastness to Light: Class 5 at 72 hours

WATER RESISTANCE

Hydrostatic Pressure Test, AATCC 127 270+ cm

FLAMMABILITY

California AB-2998: Consumer products -Flame Retardant Materials: Not Applicable

California Technical Bulletin 117 2013 Section 1 Flammability Test: Certified

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii) Federal Aviation Regulation for Flammability Resistance: Passes with flame treatment

MVSS 302 Federal Motor Vehicle Safety Standards Flammability of Interior Materials: Certified

IMO Part 8: Upholstered Furniture International Marine Organization 3.1 Cigarette Ignition: Passed

IMO Part 8: Upholstered Furniture International Marine Organization 3.2 Propane Flame: Passed

NFPA 260 National Fire Protection Association Cigarette Ignition Resistance: Certified

BS 5852:2006:Source 5 British Standard Flammability Test: Certified

Cherish may be used in California TB 133 applications with suitable fire backers.

DURABILITY Excellent. Recommended for all upholstery applications.









