# **KENYA**

# **PROPERTIES**

## **DESCRIPTION**

Embossed nubuck, pure aniline leather.

## **AVERAGE HIDE SIZE**

60.00 sq ft

#### **THICKNESS**

1.4 mm +/-0.1 mm

## **ATTRIBUTES**

Flame resistant. Water and stain repellent dyed into the leather.

## **WEIGHT**

3.50 oz +/-0.25 oz per sq ft

# **GRAIN CHARACTERISTICS**

**Embossed** 

#### **FINISH CHARACTERISTICS**

Naked

## NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

# **TEST PERFORMANCE**

## **ABRASION**

CS-10 Taber Abrasion Resistance: 3000 cycles

## **ENVIRONMENTAL**

GREENGUARD Gold Indoor Air Quality: Certified

# **FLAMMABILITY**

California Technical Bulletin 117 2013 Section E Flammability Test: Certified

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii) Federal Aviation Regulation for Flammability Resistance: Passes with flame treatment MVSS 302

Federal Motor Vehicle Safety Standards Flammability of Interior Materials: Certified

IMO Part 8: Upholstered Furniture International Marine Organization 3.1 Cigarette Ignition: Passed

IMO Part 8: Upholstered Furniture International Marine Organization 3.2 Propane Flame:

NFPA 260

Passed

National Fire Protection Association Cigarette Ignition Resistance: Certified BS 5852:2006:Source 5
British Standard Flammability Test:
Certified

## ASTM E84

Surface Burning Characteristics of Building Materials
Class B

Kenya may be used in California TB 133 applications with suitable fire backers.

## DURABILITY

Recommended for moderate to low traffic areas.

Crocking, or color transfer, may occur with excessive rubbing or exposure to moisture.





