KEYHAVEN

PROPERTIES

DESCRIPTION Embossed semi-aniline leather.

AVERAGE HIDE SIZE 54.00 sq ft

THICKNESS 1.1 mm +/-0.1 mm

ATTRIBUTES

Durable. Flame resistant. UV protected. Water and stain repellent finish.

WEIGHT 2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS Embossed

FINISH CHARACTERISTICS Hand finished

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

TEST PERFORMANCE

ABRASION

CS-10 Taber Abrasion Resistance: 1000+ cycles

ABSORPTION

AATCC 79 Absorbency of Textiles Meets Requirements

ANTIBACTERIAL

AATCC 100 Assessment of Antibacterial Finishes on Textile Materials (Quantitative): Meets Requirements

AATCC 147 Assessment of Antibacterial Activity of Textile Materials (Qualitative): Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold Indoor Air Quality: Certified

FLAMMABILITY

California Technical Bulletin 117 2013 Section E Flammability Test: Certified

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii) Federal Aviation Regulation for Flammability Resistance: Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety Standards Flammability of Interior Materials: Certified

IMO Part 8: Upholstered Furniture International Marine Organization 3.1 Cigarette Ignition: Passed

IMO Part 8: Upholstered Furniture International Marine Organization 3.2 Propane Flame: Passed NFPA 260 National Fire Protection Association Cigarette Ignition Resistance: Certified

BS 5852:2006:Source 5 British Standard Flammability Test: Certified

Keyhaven may be used in California TB 133 applications with suitable fire backers.

DURABILITY Excellent. Recommended for all upholstery applications.

Antibacterial FiberDye



O LeatherShield[™]



LEATHER

800.342.7738 garrettleather.com