SADDLE LEATHER

PROPERTIES

DESCRIPTION

Italian natural grain, semi-aniline leather.

AVERAGE HIDE SIZE

22.00 sq ft

THICKNESS

2.8 mm +/-0.1 mm

ATTRIBUTES

Natural grain with light antibacterial finish. Natural markings appear throughout each hide. Flame resistant. Water and stain repellent dyed into the leather.

WEIGHT

7.00 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Natural

FINISH CHARACTERISTICS

Light

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

TEST PERFORMANCE

ANTIBACTERIAL

AATCC 100

Assessment of Antibacterial Finishes on Textile Materials (Quantitative): Meets Requirements

AATCC 147

Assessment of Antibacterial Activity of Textile Materials (Qualitative): Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold Indoor Air Quality: Certified

LIGHTFASTNESS

AATCC 16.3 Opt 3 Colorfastness to Light: Class 5 at 72 hours

FLAMMABILITY

California Technical Bulletin 117 2013 Section E Flammability Test: Certified

FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii) Federal Aviation Regulation for Flammability Resistance: Passes with flame treatment

MVSS 302

Federal Motor Vehicle Safety Standards Flammability of Interior Materials: Certified

IMO Part 8: Upholstered Furniture International Marine Organization 3.1 Cigarette Ignition: Passed

IMO Part 8: Upholstered Furniture International Marine Organization 3.2 Propane Flame: Passed

NFPA 260

National Fire Protection Association Cigarette Ignition Resistance: Certified

BS 5852:2006:Source 5 British Standard Flammability Test: Certified

ASTM E84

Surface Burning Characteristics of **Building Materials:** Class A

Saddle Leather may be used in California TB 133 applications with suitable fire backers.

DURABILITY Excellent resistance to wear. Color may fade if exposed to direct sunlight for extended periods of time.







