

SHAGARRETT

PROPERTIES

DESCRIPTION

Italian embossed semi-aniline leather.

AVERAGE HIDE SIZE

45.00 sq ft

THICKNESS

1.1 mm +/-0.1 mm

ATTRIBUTES

Stingray embossed leather with reverse tipping and no plate lines in the main cutting area. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

WEIGHT

2.75 oz +/-0.25 oz per sq ft

GRAIN CHARACTERISTICS

Embossed stingray

FINISH CHARACTERISTICS

Reverse tipped

APPROXIMATE PATTERN REPEAT

Vertical: 12.5"

Horizontal: 14.5"

PATTERN DIRECTION

Vertical

NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

Declare.



TEST PERFORMANCE

ABRASION

CS-10 Taber Abrasion Resistance:
1400 cycles

ABSORPTION

ASTM D751 Water Resistance
Hydrostatic Pressure Test:
Exceeds Requirements 150+ cm

AATCC 79-2010
Absorbency of Textiles:
Meets Requirements

ANTIBACTERIAL

AATCC 100
Assessment of Antibacterial Finishes
on Textile Materials (Quantitative):
Meets Requirements

AATCC 147
Assessment of Antibacterial Activity
of Textile Materials (Qualitative):
Meets Requirements

ENVIRONMENTAL

GREENGUARD Gold
Indoor Air Quality:
Certified

FLAMMABILITY

California AB-2998;
Consumer products -
Flame Retardant Materials:
Passed

California Technical Bulletin
117 2013 Section E Flammability Test:
Certified

FAR 25.853 (a) Am. 25-116, App. F,
Part I (a)(1)(ii) Federal Aviation
Regulation for Flammability Resistance:
Passes with flame treatment
NFPA 260
National Fire Protection Association
Cigarette Ignition Resistance:
Certified

BS 5852:2006:Source 5
British Standard Flammability Test:
Certified

*Shagarrett may be used in California
TB 133 applications with suitable fire
backers.*

DURABILITY Excellent. Recommended for all upholstery applications, especially high traffic areas.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818



LeatherShield™



Antibacterial



FiberDye™

GARRETT

LEATHER

800.342.7738
garrettleather.com