

# SHAGARRETT

## PROPERTIES

### DESCRIPTION

Italian embossed semi-aniline leather.

### AVERAGE HIDE SIZE

45.00 sq ft

### THICKNESS

1.1 mm +/-0.1 mm

### ATTRIBUTES

Stingray embossed leather with reverse tipping and no plate lines. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

### WEIGHT

2.75 oz +/-0.25 oz per sq ft

### GRAIN CHARACTERISTICS

Embossed stingray

### FINISH CHARACTERISTICS

Reverse tipped

### APPROXIMATE PATTERN REPEAT

Vertical: 12.5"  
Horizontal: 14.5"

### PATTERN DIRECTION

Vertical

### NON-TOXIC COMPOSITION

Our leathers are not made with nor contain conflict minerals, POPs, PVC, BPA, PBDEs, plasticizers, heavy metals, or phthalates.

## TEST PERFORMANCE

### ABRASION

CS-10 Taber Abrasion Resistance:  
1400 cycles

### ABSORPTION

AATCC 79-2010  
Absorbency of Textiles:  
Meets Requirements

### ANTIBACTERIAL

AATCC 100  
Assessment of Antibacterial Finishes  
on Textile Materials (Quantitative):  
Meets Requirements

### AATCC 147

Assessment of Antibacterial Activity  
of Textile Materials (Qualitative):  
Meets Requirements

### ENVIRONMENTAL

GREENGUARD Gold  
Indoor Air Quality:  
Certified

### FLAMMABILITY

California AB-2998;  
Consumer products -  
Flame Retardant Materials:  
Passed

California Technical Bulletin  
117 2013 Section E Flammability Test:  
Certified

FAR 25.853 (a) Am. 25-116, App. F,  
Part I (a)(1)(ii) Federal Aviation  
Regulation for Flammability Resistance:  
Passes with flame treatment

### NFPA 260

National Fire Protection Association  
Cigarette Ignition Resistance:  
Certified

### BS 5852:2006:Source 5

British Standard Flammability Test:  
Certified

*Shagarrett may be used in California  
TB 133 applications with suitable fire  
backers.*

**DURABILITY** Excellent. Recommended for all upholstery applications, especially high traffic areas.



800.342.7738  
garrettleather.com